

9.2-CHANNEL NETWORK A/V RECEIVER



Get Together for a Gold-Class Film Experience

With more distortion-free power, IMAX® Enhanced* certification for IMAX® remastered movies, and Dolby Atmos® or DTS:X® surround-sound reproduction through 5.2.4 channels, the Integra DRX-4.3 opens the door to gold-class home theater complete with powered or wireless audio distribution to your favorite rooms. * Enabled with a future firmware update.

VIDEO & AUDIO SUPPORT

- 9-ch amp supports 5.2.4, 7.2.2, or 7.2.4*1 Dolby Atmos® and DTS:X® playback
- IMAX® Enhanced*2 certified for IMAX® digital remasters
- Dolby Atmos Height Virtualization*2 technology
- Dolby Surround® and DTS® Neural:X upmixing technology
- 4K/60p, HDR (HDR10, HLG, Dolby Vision™), BT.2020, and 4:4:4/24-bit video passthrough with HDCP 2.2
- 11.2-channel pre-outs and DSP processing for 7.2.4-ch*1 layouts
- Separate switching Zone 2 outputs and assignable Zone 3 outputs with DACs for unique or synced D/A source distribution (including HDMI/SPDIF^{*3})
- Zone 2 pre-/line-out/Zone B line-out shares unique/synced D/A audio^{*4} in both rooms or connect a compatible wireless headphone transmitter
- Built-in phono equalizer (MM) and SACD playback via HDMI® (2.8 MHz/2-ch/multi)
- AccuEQ Advance 9-point calibration with subwoofer EQ and AccuReflex™
- HDMI Sub/Zone 2 output shares media to a projector or second display
- Easy DSP-based Vocal Enhancer clarifies in-program dialog

AMPLIFICATION TECHNOLOGY

- 100 W per channel (8 ohms, 20 Hz–20 kHz, 0.08% THD, 2-ch driven, FTC)
- THX® Certified Select[™] for Theater Reference Sound
- Low-impedance amp system with 4-ohm speaker-driving capability
- Massive custom transformer and customized 10,000 μF capacitors
- · Thick copper bus-bar connects capacitors to amplifiers
- Hand-selected audio-tuned parts on separated digital/analog circuit boards
- Extruded anti-resonant aluminum heat-sink
- Non-phase-shift amp-circuit topology with 10 Hz-100 kHz frequency response
- High-performance 384 kHz/32-bit D/A conversion (AKM AK4458)
- VLSC[™] (Vector Linear Shaping Circuitry) filtering technology (Front L/R)
- Front L/R speaker bi-amping capability in 5.2/7.2/5.2.2-ch configuration
- Independent tone controls for all channels (including Zone 2)

NETWORK FEATURES AND MULTI-ZONE AUDIO

- Quad-core SoC (System on a Chip) supports 802.11ac 2x2 MIMO*5 Wi-Fi®
- Supports Amazon Music, Spotify[®], TIDAL, TuneIn, Pandora[®], and Deezer^{*6}
- $\bullet\,$ Works with Sonos certified for the Sonos Home Sound System $^{\!\star 7}$
- Chromecast built-in^{*8} and voice control with the Google Assistant^{*9}
 AirPlay 2 multi-room audio and voice control with Siri[®]*10
- DTS Play-Fi® multi-room audio via Integra Music Control App*11
- FlareConnect^{™*12} multi-zone audio with compatible components
- FlareConnect^{***} ¹² multi-zone audio with compatible component
 Supports Integra Remote control and music streaming app^{*11}
- Hi-Res Audio playback via network (DSD 11.2 MHz/5.6 MHz/2.8 MHz*13; FLAC, WAV [RIFF], AIFF, and ALAC to 192 kHz/24-bit*14)

AUDIO-VIDEO CONNECTIONS

- 7 HDMI inputs (1 front), Main output (ARC), Sub/Zone 2 output
- 2 digital audio inputs (1 optical and 1 gold-plated coaxial, assignable)
- 7 gold-plated analog audio inputs (1 front)

- Gold-plated phono input (MM) for turntable connection
- USB input (5 V/1 A) for audio playback (rear)
- 1/8" (3.5 mm) AccuEQ Advance setup mic input (front)
- 3 gold-plated composite video inputs (1 front)
- 1 gold-plated component video input (assignable)
- Gold-plated guarter-inch headphone jack
- 11 banana-plug-ready transparent gold speaker posts (including Zone 2)
- 11.2-channel pre-outs (including Zone 3 pre-/line-out)
- Gold-plated Zone 2 pre-/line-out, Zone B line-level output (analog RCA)
- 2 subwoofer pre-outs

CUSTOM INTEGRATION FEATURES

- Bi-directional Ethernet LAN for IP control and dealer setup
- RS-232 serial port for external control and automation
- 2 IR inputs and 1 output
- Programmable 12 V trigger-outs with adjustable delay (A: 100 mA, B: 25 mA, C: 25 mA)
- Dealer-settings memory storage and recall function
- OSD output function for installers
- Thick detachable IEC power cable
- Optional rack-mount kit (IRK-155-3D)

ADDITIONAL FEATURES

- Aluminum front panel and volume control
- Stereo Assign Mode supports Height-channel playback
- Volume memory-presets for A/V inputs via front panel
- Bluetooth® Version 4.2 (Profile: A2DP v1.2, AVRCP v1.3)
- Advanced Music Optimizer[™] improves quality of compressed audio
- High-definition GUI over HDMI featuring source input/output data display
- Super Resolution 1080p to 4K video upscaling via HDMI
- Volume memory-presets for A/V inputs via front panel
- Sleep timer, HDMI passthrough, and network standby
- 40 FM/AM/internet radio presets with station-naming (10 characters)
- A/V Sync Control (Up to 500 ms in 1 ms Steps at 48 kHz)
- Crossover Adjustment (40/45/50/55/60/70/80/90/100/110/120/130/150/180/200 Hz)
- 3-Mode display dimmer (Normal/Dim/Dimmer)

*1 Requires connection of an external power amp via multichannel pre-outs. *2 Enabled with a future firmware update. *3 Zone 2 HDMI audio is available on inputs 1-3. SPDIF and HDMI support PCM signals only. Zone 3 supports analogi/NET/Bluetoth. Simultaneous playback of multiple audio sources is enabled in Main, Zone 2, and Zone 3. Output via Zone 2 speaker outputs and Zone 2/Zone B line-out is enabled. *4 When set to Zone B, the same encoded or PCM audio playback in Main is enabled in Zone B. '5 Some countries or regions have regulations that affect wrieless signal strength and the use of Wi-Fi channels. *6 Service availability varies with region, and a paid subscription may be required to access some or all features. *7 Requires a Sonos Connect (sold separately). Sonos Music Control App is available free for iPhone*, iPad*, and Android** devices. Please check device and OS requirements before download and installation. *8 The unit may automatically download and apply an Over-the-Air software update during setup. 9 Voice control requires a smart speaker featuring the Google Assistant. *10 Voice control with Sin requires an Apple HomePod*. *11 Available free for iPhone, iPad, and Android devices. Please check device and OS requirements before download and installation. *12 FlareConnect is a proprietary network protocol that shares audio between compatible products. For details on product compatibility, please visit the Integra website. *13 Converted to PCM. Playback not guaranteed via wireless LAN. *14 Supported sampling rates may vary depending on network environment. ALAC is supported to a maximum 96 kHz.

9.2-CHANNEL NETWORK A/V RECEIVER







COMPATIBLE DOLBY VISION













































225 W/Ch at 6 Ohms, 1 kHz, 10%,

100 W/Ch at 8 Ohms, 20 Hz-20 kHz, 0.08%,

200 mV rms/47 k-Ohms (Line/Unbalance)

3.5 mV rms/47 k-Ohms (Phono MM)

1 V rms/470 Ohms (Subwoofer Pre-out)

0.08% (20 Hz-20 kHz, Half Power)

1 Channel Driven,

2 Channels Driven, FTC

250 W (3 Ohms, Front)

220 W (4 Ohms, Front) 130 W (8 Ohms, Front)

200 mV rms/470 Ohms



SPECIFICATIONS

AMPLIFIER SECTION

Power Output Front L/R

Dynamic Power:

Input Sensitivity and Impedance:

THD+N (Total Harmonic Distortion + Noise): Rated RCA Output Level and Impedance:

Phono Overload: Frequency Response:

Signal-to-Noise Ratio:

(Zone 2 Pre-/Line-out/Zone B Line-out) 70 mV (MM 1 kHz, 0.5%) 10 Hz-100 kHz/+1 dB, -3 dB (Direct Mode) ±10 dB, 20 Hz (Bass) Tone Control:

±10 dB, 20 kHz (Treble) 106 dB (IHF-A, LINE) 80 dB (IHF-A, PHONO)

Speaker Impedance: 4 Ohms-16 Ohms VIDEO SECTION

Signal Level 1 Vp-p/75 Ohms Composite Video 1 Vp-p/75 Ohms Component Video (Y) 0.7 Vp-p/75 Ohms Component Video (Pb/Pr)

TUNER SECTION

FM 87 5 MHz-107 9 MHz Tuning Frequency Range: AM 530 kHz-1,710 kHz

FM/AM Preset Memory: 40 Stations

GENERAL

AC 120 V~, 60 Hz Power Supply: Power Consumption: 750 W


Stand-by Power Consumption: 0.15 W Dimensions (W x H x D):


17 ¹/₈" x 6 ⁷/₈" x 14 ¹³/₁₆" (435 x 174 x 376.5 mm) 24.7 lbs. (11.2 kg)

Weight: CARTON

Dimensions (W x H x D):

22 ¹/₁₆" x 12" x 18 ³/₈" (560 x 305 x 467 mm) Weight: 30.9 lbs. (14.0 kg)





Due to a policy of continuous product improvement, Integra reserves the right to change specifications and appearance without notice. THX and the THX logo are trademarks of THX Ltd., registered in the U.S. and other countries. THX CERTIFIED SELECT and the THX SELECT application icon are trademarks of THX Ltd. Dolby, Dolby Atmos, Dolby Surround, Dolby Vision, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patents, see hipty-lipstenis.dis.com. Manufactured under license from IDTS Licensing, Limited DTS, the Symbol, DTS and the Symbol objective, DTSX: And the DTSX Mogo, DTS NeuraliX and the DTS NeuraliX logo, and Play-Fi and the Play-Fi logo are registered trademarks or OTTS, inc. All Rights Reserved. Manufactured under license from IMAX Corporation in MAX* is a registered trademark of IMAX Corporation in the United States and other countries. SAIN Rights Reserved. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of IMAX Corporation is the United States and other countries. SONOS is a trademark of SONOS, inc. The Bluetooth's word mark and logos are owned by the Bluetooth ISIG, linc. Apple, AirPlay, IPad., AirPlay, IPad.,